

Mark 1

Basin Faucet 6909-91-80CP

INTRODUCTION:

Designed main body style as square shape, the aesthetics of symmetry exudes a stylish and charming atmosphere. With R angle processed, it softens the sharp angle of hard steel, and brings soft and elegant atmosphere to a bathroom space.

DESCRIPTION:

- 1.Swiveling spout can be adjusted by consumer request and passed up to 50,000 turns test.
- 2.Ceramic valve with CERAMTEC ceramic disc / (Germany)
- 3.Handle can be moved upward to 25° to adjust water flow from closed position, hot and cold water controlled by swinging handle 45° on left and right sides.
- 4.Stainless steel braided hose with SANTOPRENE tube (meets NSF approval), can bear 15Kg/cm² water pressure and 120°C heat.
- 5.Stainless steel braided hose with M10 x 1.0mm (Male thread connected to faucet body) and 1/2"-14NPSM (Female thread connected to water supply system).
- 6.Aerator with removable flow restrictor (2.2 GPM max.), end-user can remove it for large water flow request.
- 7.Brass with Chrome plated meets ASTM-SC2 standard.
- 8.Handle material meets JIS 3771 Standard.
- 9.Faucet body material meets JIS 3604 Standard.

Fixing Kits:

- 1.Mounting Bolt*1
- Rubber Washer*1
- Nut*1
- Bracket*1

AWARD: